DINI ARGEO

A RICE LAKE WEIGHING SYSTEMS COMPANY

WEPWLI-PRO

WEICOMP Pro Stainless Steel Pallet-Weighing Scale



WEICOMP

Fast, accurate, easy to use, transport and position stainless steel pallet scale, according to one's weighing needs.

- Ideal for use in harsh environments or with high hygiene requirements. Available in approved version for legal-for-trade use.

Working in cooperation with:


67 PESAGE
RUE DE LA VEDETTE 31 - 67700 SAVERNE FRANCE
Tel. 0033388042020 - Fax 0033388042029

The best solution for advanced industrial applications

TECHNICAL FEATURES - PALLET WEIGHER

- Stainless steel tubular frame, complete with adjustable feet.
- Level bubble, wheels and transport handle.
- Connection cable to the indicator, 3 meters long.
- Operating temperature: -10° / +40° C.
- Digital calibration and set-up from keyboard or from PC with DINITOOLS.

CONNECTOR PINOUT



Pin	Signal	Color
1	SIG+	Pink
2	SIG-	Yellow
3	SENSE+	Green
4	SENSE-	White
5	EXC-	Grey
6	EXC+	Brown
7	GND	Shield

-

MAIN FUNCTIONS

- Net or gross weight control, according to sample.
- Take away weight control.
- Piece counting and control.
- Weighing in percentages.
- Weight conversion to lb, or with a freely programmable conversion factor.
- Totalization.
- Formulation.
- Automatic tare.
- Manual dosing.

TECHNICAL FEATURES - WEIGHT INDICATOR

- Multifunction weight indicator in AISI 304 stainless steel.
- 25mm 6-digit LCD display with interactive RGB color backlighting.
- 5-key numeric function keypad.
- Support bracket with adjustable angle, with fixing holes.
- Load cell connection to the weight indicator via IP67 connector.
- Internal power supply 230 VAC / 12 VDC, with 1,5m cable and EU or UK plug.
- Internal rechargeable NiMH battery, with approx. 80h autonomy; *Charging time approximately 6 hours.*
- Configurable energy saving functions to minimize energy consumption.

INPUT/OUTPUT COMMUNICATION PORTS

- RS232 on screw terminals for connection to Dini Argeo PCs/printers.
- RS232 on AMP connector, with CTS, for connection to
- Dini Argeo printers.
- RS485 on screw terminals for connection to PCs/PLCs,
- with Modbus RTU or ASCII protocol.
- USB-C for connection to PCs.
- Customizable weight communication string.

Optional:

- WiFi port.
- Ethernet TCP/IP port (includes Modbus-TCP protocol).

DETAIL 1



Optional column.

VERSIONS

Available versions

Code	l x w x h (mm)	Max (kg)	d (kg)	M 2R (kg)
WEPWLI	1260 x 800 x 75	600 / 1500 / 2000	0,2 / 0,5/1	--
WEPWLIM M	1260 x 800 x 75	1000 / 2000	--	0,5 / 1

www.diniargeo.com



DINI ARGEO FRANCE sarl
France

DINI ARGEO GMBH
Germany

DINI ARGEO UK Ltd
United Kingdom

DINI ARGEO WEIGHING INSTRUMENTS Ltd
China

DINI ARGEO OCEANIA
Australia

DINI ARGEO
A RICE LAKE WEIGHING SYSTEMS COMPANY

COMPANY HEADQUARTERS
Via Della Fisica, 20
41042 Spezzano di Fiorano Modena • Italy
Tel. +39.0536 843418

67 PESAGE
RUE DE LA VEDETTE 31 - 67700 SAVERNE FRANCE
Tel. 0033388042020 - Fax 0033388042029
contact@67pesage.com

SALES AND TECHNICAL ASSISTANCE SERVICE

All the specifications and images can be subject to variations and upgrades without prior notice.